

AC-DIN-PW60

Power Distribution Block



CONTACT US

P: 080-42049370
E: info@sonetnix.com
A: #14, HD Tower, Green Garden Main Road,
 K.Channasandra ,Bengaluru – 560 113

www.sonetnix.com

- *AC-DIN-PW60 It features universal AC input and at the same time accepts DC input voltage, low power consumption, high efficiency, high reliability, reinforced isolation.*

OTHER FEATURE

- ✓ □ Universal 110-230VAC Power supply
- ✓ □ Operating ambient temperature range: -25°C to +0°C □
- ✓ □ Output short circuit, over-current, over-voltage protection □
- ✓ □ High efficiency, High reliability □
- ✓ □ Regulated output, low ripple & noise □
- ✓ □ Easy to installation - DIN-RAIL outtable
- ✓ □ The converters are widely used in Lighting automation application, industrial, office and civil applications.

— ■ Operating Voltage	: 20-230VAC
— ■ Output Power	: 60 watts
— ■ Nominal output Voltage & Current	: 12VDC @5A
— ■ Operating Temperature	: 0 - 45 °c
— ■ S-NET Power Usage	: 1.08 Watt (0.09A @12Volts)

— ■ **PWR** : Red LED illuminates when AC power is applied to the power port

— ■ **INPUT (1-2)** : (1) 2 PIN 5.08mm Screw terminal block

— ■ **OUTPUT (1-6)** : (6) 2 PIN 3.81mm detachable terminal blocks